# HP PageWide XL Pro Sheet-feeder for HP PageWide XL Pro Printers



Fully integrated large-format sheet feeder<sup>1</sup> to speed up your end-to-end cut-sheet workflow



### End-to-end cut sheet workflow

- Accept demands for different sizes and media types from 120 to 1050 gsm media or up to 2 mm thick sheet.
- Gain flexibility for short runs with fast feeding of cut sheet and boards up to 5 cm of media height from A2 to B1 sizes.

### **High productivity**

- Accommodate urgent demands with a first page out in 20 seconds and total throughput up to 500 m<sup>2</sup>/hr.
- Convenient sheet feeder delivers intuitive operation with simple, guided instructions from the front panel.

### Fully integrated solution

- Reliable workflow includes bi-directional communication between the printer and sheet feeder.
- Easily monitor your sheet feeder from the printer's front panel, HP SmartStream, or certified RIP solution.

#### **Technical specifications**

General	Capacity	Up to 50 mm (1,97 in) total thickness
	Media width	420 - 1020 mm (16,5 – 40,15 in)
	Media length	580 - 850 mm (22,8 – 33,5 in)
	Media weight	120 - 1050 gsm
	Total stacking height	0,1 - 2 mm (3.9 – 78,7 mil)
Paper handling	Maximum feeding speed	12 ips cut sheet feeding speedSustained throughput: up to 500 m²/h (5300 ft²/h)
	Max sheet/board size supported	B1 landscape
	Min sheet/board size supported	A2 portrait
	Paper set supported	Full cut sheet set supported by the printer
Connectivity		Power provided by printer through communication cable
Dimensions	Dimensions with packaging	1740 x 1070 x 1970 mm (68,5 x 42,1 x 77,6 in)
	Dimensions without packaging	1600 x 2200 x 1200 mm (63 x 87,6 x 47,2 in) height adjustable according to printer version
Weight	Weight with packaging	260±10 Kg (575±25 lb)
	Weight without packaging	190±30 Kg (419 ± 66 lb)
Environmental	Operating temperature	5 to 40ºC (41 to 104 ºF)
	Recommended temperature	20 to 80 RH, depending on the media type
	Operating humidity	65 W (maximum normal load) / 36 W (only with fan working)
Acoustic	Sound pressure	Idle <38 dB(A); Operating 60 dB(A) (Fast mode)
	Sound power (printing)	Idle <5.8 B(A); Operating ≤7.8 B(A) (Fast Mode)
Power	Consumption	65 W (maximum normal load) / 36 W (only with fan working)
	Voltage range	Input voltage (auto ranging) 200-240V (+-10%), 50/60 Hz (+- 3Hz), 0.5 A
Certification	Safety	IEC 60950-1+A1+A2 and IEC 62368-1 2nd ed. compliant; USA and Canada (CSA listed); EU (LVD and EN 60950-1 and 62368-1 compliant); Russia, Belarus, and Kazakhstan (EAC)
	Electromagnetic	Compliant with Class A requirements, including USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC).
	Environmental	CE marking (including RoHS, WEEE, REACH). In compliance with WW RoHS materials restriction requirements in China, Korea, India, Vietnam, Turkey, Serbia and Ukraine
Warranty		90 days
		HP PageWide XL Pro 5200 MFP
Compatibility		HP PageWide XL Pro 8200 MFP
		HP PageWide XL Pro 10000 Printer

## **Ordering information**

Product 8SB05A	HP PageWide XL Pro Sheet-feeder	
----------------	---------------------------------	--



- 2 Bridge feeding sheets to the printer
- 3 Rear tray stop / Lateral tray stop
- 5 Calibration wheel
- 6 Adjustable height
- ensure alignment
- 8 Easy access to rolls and input tray

© Copyright 2021 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.



Adobe, Acrobat, Illustrator, Photoshop, and PostScript are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries. Intel is a trademark of Intel Corporation in the U.S. and other countries. Windows is a U.S. registered trademark of Microsoft Corporation.