HP DesignJet XL 3600 Multifunction Printer series



Experience a new standard with the most immediate and robust HP MFP in the market²



IMMEDIATE RESULTS—Immediate prints, no warm up time²

- Free up your time with radically simple and fast batch PDF printing using HP Click software.
- Quickly access your personal and group folders from the touchscreen, so you can print and share right away.³
- Easily digitize your projects with automated scanning, user-centric quicksets, and postediting capabilities.

A NEW STANDARD—Experience extreme reliability

- Built with a robust design for demanding environments.²
- Best fit for your office with up to 30% smaller footprint and the most quiet operation.⁴
- Flawless user experience thanks to automatic media loading and print stacking up to 100 pages.
- Get low running costs, with mono and color prints at the same price and using up to 10X less energy.²

SECURE—Best in class security in Large Format Printing¹

- Rely on the best network protection with features like HP Secure Boot and whitelisting.¹
- Control who accesses the printer and its confidential documents with secure user authentication.
- Keep your fleet secure at any time with HP JetAdvantage Security Manager.

For more information, please visit http://www.hp.com/go/designjetxl3600

Dynamic security enabled printer. Only intended to be used with cartridges using an HP original chip. Cartridges using a non-HP chip may not work, and those that work today may not work in the future. More at: http://www.hp.com/go/learnaboutsupplies

² Up to 10 times less energy consumption based on internal HP testing for specific use scenarios. Operational costs based on low-volume LED technology under \$17,000 USD in the market as of November, 2018. Operational costs consist of supplies and service costs. For testing criteria, see http://www.hp.com/go/designjetxlclaims. ³ Using Lightweight Directory Access Protocol (LDAP).

¹⁻ Advanced embedded security features are based on HP review of 2019 published embedded security features of competitive printers, as of February 2019.

^{* 30%} smaller footprint based on comparable printers using LED technology and capable of printing 4-6 D/A1 pages per minute and which represent more than 40% of the share of low-volume LED printers in the US and Europe according to IDC as of November, 2018. Measure done considering operational footprint (with the media drawer open). Most quiet operation based on comparable printers using LED technology and capable of printing 4-6 D/A1 pages per minute and which represent more than 40% of the share of low-volume LED printers in the US and Europe according to IDC as of November, 2018. Measure done considering operational footprint (with the media drawer open). Most quiet operation based on comparable printers using LED technology and capable of printing 4-6 D/A1 pages per minute and which represent more than 70% of the share of low-volume LED printers in the US and Europe according to IDC as of November, 2018. Most quiet according to internal HP testing of operation mode and ready/sound mode sound pressure (plain paper, line drawing, normal mode) compared to published specifications of competitive printers. For testing criteria, see http://www.hp.com/go/designjetxlclaims.

Technical specifications

Print speed 190 A I/hr 20 oscAl 21	Print	
3.0 /mm Har resolution Hp 12 AdD x 1200 optimized dpi Bet hologin HP Thermal Insign Bet hologin HP Thermal Insign Bet hologin De Thesade (C, M, MK, Y) pagment-based (mR) Bet hologin De Thesade (C, M, MK, Y) pagment-based (mR) Bet hologin De Thesade (C, M, MK, Y) pagment-based (mR) Bet hologin De Thesade (C, M, MK, Y) pagment-based (mR) Scan scalution De Thesade (C, M, MK, Y) pagment-based (mR) Scan scalution De Thesade (C, M, MK, Y) pagment-based (mR) Scan scalution De Thesade (C, MK, MK, Y) pagment-based (MR) Scan scalution De Thesade (C, MK, MK, Y) pagment-based (MR) Scan scalution De Thesade (MR) Scan scalution De Thesade (MR) Scan scalution De Thesade (MR) Scan scalution De Standard (MR) <td>Print speed</td> <td>180 A1/hr</td>	Print speed	180 A1/hr
Print resolution Up to 2.400 x 1200 optimized dpi Enronlogy UP Thermal Inlight Richnology UP Thermal Inlight Richnology 0.11 (E. M. V.C. m/K, p.R) Marthance 0.11 (E. M. V.C. m/K, p.R) Marthance 0.11 (E. M. V.C. m/K, p.R) Marthance 0.11 (E. M. V.C. m/K, p.R) Sam speed Caser Ub to 7.52 cm/Sec Ecolor.200 dpl, up to 25.4 cm/Sec (grayscale, 200 dpl) Sam speed Caser Ub to 7.52 cm/Sec Ecolor.200 dpl, up to 25.4 cm/Sec (grayscale, 200 dpl) Sam speed Caser Ub to 7.52 cm/Sec Ecolor.200 dpl, up to 25.4 cm/Sec (grayscale, 200 dpl) Sam speed Dal & B000 mm (PEG).110 x 15.000 mm (PEF); 914 x 8000 mm (PDF); Thickness DB is 7.600 fbr 2005Csigt Printer) Sam destination USS, shared envolve foldier, sona page path for sheet and carboard originals Martinations A, A, A, A, A, A, A, B, C, D, D Sam set Sace 2710 x 2710 mm valdtu, pu to 200 mm (PEG).11 mm Sam set Sace 2710 x 2710 mm valdtu, pu to 200 mm (PEG).11 mm Sam set Sace 2710 x 2710 mm valdtu, pu to 200 mm (PEG).11 mm Sam set Sace 2710 x 2710 mm valdtu, pu to 200 mm (PEG).11 mm Sam set Sace A, A, A, A, A		
Technology HP Thermal Insign Fisk pages Due-Board C, G, M, KY, MP, MP, MP, MP, MP, MP, MP, MP, MP, MP		
ins types De-based (C, G, M, SY, Typermet-based (m) ins dops O, D, B(, M, Y, G, NK, D, M, S, OK, S, D, S, S, Charlow, C, S, D, S,		
is drop 6.pl (C, M, X, G, M2, P) Prothads 1 (C, M, X, G, M2, P) Minimum line width 0.02 mm (HP-GL/2 addressable): Multifunction capabilities Scan speed Scan Ub to 7.62 m/sec (rolps 200 dpl), up to 25.4 cm/sec (grayscale, 200 dpl) (Sop Ub to 7.62 m/sec (rolps 200 dpl), up to 25.4 cm/sec (grayscale, 200 dpl) (Sop Ub to 7.62 m/sec (rolps 200 dpl), up to 25.4 cm/sec (grayscale, 200 dpl) (Sop Ub to 500 dpl Maximum scan sec (Sop Ub to 7.62 m/sec (rolps 200 dpl), up to 25.4 cm/sec (grayscale, 200 dpl) (Sop Ub to 500 dpl Maximum scan sec (Sop Ub to 7.62 m/sec (rolps 200 dpl), up to 25.4 cm/sec (grayscale, 200 dpl) (Sop Ub to 500 dpl Maximum scan sec (Sop Ub to 7.62 m/sec (rolps 200 dpl), up to 25.4 cm/sec (grayscale, 200 dpl) (Sop Ub to 500 dpl Maximum scan sec (Sop Ub to 7.62 m/sec (rolps 200 dpl), up to 25.4 cm/sec (grayscale, 200 dpl) (Sop Ub to 50.8 dpl) (Sop Ub to 200 dpl) (Sop Ub to 50.8 dpl) (S		
Partheads 1 C, M, Y, G, mK, ppl Partheads 1 C, M, Y, G, mK, ppl Partheads 0.02 mm RHP-GL/2 addressable) Multifunction capabilities Sam Ub to 1.5.2 m/sec (color, 200 dp), up to 2.5.4 m/sec (grayscale, 200 dp) Gain resolution Up to 600 dpi Maximum Line width Dec 2 mm/sec (color, 200 dp), up to 2.5.4 m/sec (grayscale, 200 dp) Maximum Line width Dec 2 mm/sec (color, 200 dp), up to 2.5.4 m/sec (grayscale, 200 dp) Maximum Sam Sace 91.4 x8000 mm (PEG, ETF, PDF Ger Op SCript Printer) Sam destination UBS, Sam enterwork (ddor, printer HDD, enall Media Sec resolution Sam sec stage Media Sec resolution (color, 200 dp), up to 2.9.0 m length, 3-in core (default or 2-in core (ptional) Sam dot sheets 210 x 271 to 914 x 121 mm Sam sec stage Sam Sam Sam Sam PD to 3.7 mm (Db to 19.7 mi) Sam sec stage (Color, 200 dp), up to 2.9 m length, 3-in core (default or 2-in core (ptional) Sam		
in accuracy to 11% in accuracy to 12% in accuracy to 17.62 m/sec (color, 200 dp), up to 25.4 m/sec (grayscale, 200 dp) (200 H) to 17.62 m/sec (color, 200 dp), up to 25.4 m/sec (grayscale, 200 dp) (200 H) to 15.24 m/sec (color, 200 dp), up to 25.4 m/sec (grayscale, 200 dp) (200 H) to 15.24 m/sec (color, 200 dp), up to 25.4 m/sec (grayscale, 200 dp) (200 H) to 15.24 m/sec (color, 200 dp), up to 25.4 m/sec (grayscale, 200 dp) (200 H) (200 H		
Maintfunction capabilities 0.22 mm (HP-GL/2 addressable); Multifunction capabilities Scan: Up to 7.62 m/sec (color, 200 dp), up to 25.4 m/sec (grayscale, 200 dp) Scan resolution Up to 500 dp. Maintfunction capabilities Scan: Up to 7.62 m/sec (color, 200 dp.), up to 25.4 m/sec (grayscale, 200 dp) Scan resolution Up to 500 dp. Meanum scan size 91.4 x8000 mm (HP-GL); at 0.15,000 mm (HP-D; Thickness 0.8 mm, Scan format UP65, TEF, IPE FOF for PostScript Printer) Scan destination US8, shared network flodde, printer HD0, email Media Scanes: straight-Hinologi Scan paper path for sheet and cardbaard originals State state 210 v 229 to 91.4 v 121 9 mm State state 210 v 229 to 91.4 v 121 9 mm Media Scanes: straight-Hinologi Scan paper path for sheet and cardbaard originals State state 210 v 229 to 91.4 v 127 mill Applications Up of 20 million (State straight-Hinologi Scan paper path for sheet and cardbaard originals Standard sheet 270 v 219 to 91.4 v 200 State state 210 v 229 to 91.4 v 210 mm Applications Up of dos/state state state strais Up of dos dos		
Multifunction capabilities Scan speed Sear Up to 15.2 em/sec (color, 200 dpl), up to 25.4 em/sec (grayscale, 200 dpl) Scan resolution Up to 50.0 dpl Scan resolution 91.4 & 6000 mm (IPEG), 61.0 x 15,000 mm (IPEF), 91.4 x 8000 mm (IPEF); Scan resolution UBB, there of retwork folder, primter HDD, email Wedia Scan resolution Scan resolution UBB, there of retwork folder, primter HDD, email Wedia Scan resolution Scan retwork Scan retwork for thorpathy in the retwork folder, primter HDD, email Wedia Scan retwork for thorpathy in the retwork folder, primter HDD, email Scan retwork for thorpathy in the retwork folder, primter HDD, email Scan retwork for thorpathy in the retwork folder, primter HDD, email Scan retwork for thorpathy in the retwork folder, primter HDD, email Scan retwork folder, primter HDD, email Scan retwork for thorpathy in the retwork folder, primter HDD, email Scan retwork folder, primter HDD, email Scan retwork for the retwork folder, primter HDD, email Scan retwork folder, primter HDD, email Scan retwork folder, primter HD, PS, PL, PS, PL		
Scin speed Scan Up to 17.6 zm/sec folior, 200 dpi) up to 25.4 mm/sec (grayscale, 200 dpi) Scin resolution Up to 500 dpi Maximum scan size 91.4 x8000 mm (UPER); 610.x 15,000 mm (UFF); 914 x 8000 mm (UPER); Scin resolution Up to 500 dpi Maximum scan size 91.4 x8000 mm (UPER); Scin remat JPES, TIF, FDF GM on PostScript Printer) Scan destinations USB, showed network: folder, printer HDD, email Media Scine remat Scan unternation in the scine remath scine remain scine remains Scine remains Scan unternation in the scine remath scine remains Scine remains Scan unternation in the scine remains Scine remains Scan unternation in the scine remains Scine remains Method Scine remains Scine remains Scine remains Scine r		0.02 mm (mmul/2 addressable),
Copy: Up to 15.24 cm/sec (doip, up to 2.54 cm/sec (grayscale, 200 dp)) Meakimum scan size 914 x 8000 mm (JPEG); 610 x 15.000 mm (TIFF); 914 x 8000 mm (PDF); Dirkinass 0.8 mm; Scan format JPEG, TFR PDF (for PostScript Printer) Scan destinations USB, shared network folder, printer HDD, email Media		Scap: Up to 7.62 cm/coc (color 200 dpi) up to 25.4 cm/coc (gravecalo 200 dpi)
Maximum Scan Size 914 x 8000 mm (PER); 610 x 15,000 mm (TEF); 914 x 8000 mm (PDF); Thickness 0.8 mm; San format PFE, TFF, PDF (for PostScript Printer) San deminations USB, shared network (tolder, printer HOD, email Wedia		Copy: Up to 15.24 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi)
Thickness 0.8 mm; Scan format JPEG, TFF, PDF (for PostScript Printer HDD, email Media Media Scan estimations Sigs, shared network folder, printer HDD, email Media Scanner straight-Hough scan paper path for sheet and cardboard originals Sinet size 210 x 2710 0 144 x 121 9 mm Boll size 270 to 19 -4 mm width, up to 200-m length, 3 -in core (default) or 2-in core (optional) Standard sheets At, A2, A1, A0 (A, A) (A, B), C, D, D Grammage 60 to 28 g/m² Memory 128 of Bill processing? Hickness Une dawings, Maps, Orthophotos; Presentations; Renderings Memory 128 of Bill processing? Hitchess Gigabil Ethernet (1000Base-T), supporting the following standards: TCPIIP BootP/DHCP (IP-4 only), DHCP (F), TTP IPW (anly), SNMP (V), A2, v3), Apple Bonput Compatible; WS Discover, It, Imbedded Web Server (TTP); HTTTS, DB, SCS, VTP (email, Auch PEAR, LAP-TA3, DFS Print languages (standard) Non-PostScript Printer: Adobe PESScript A: Adobe PE 17, IP-C24, JP-RTL, TFF, JPEG, CALS G4, Non-PostScript Printer: Adobe POSScript A: Adobe PDF 17, AP-C24, JP-RTL, TFF, JPEG, CALS G4, Non-PostScript Printer: Adobe POSScript A: Adobe PDF 17, AP-C24, JP-RTL, TFF, JPEG, CALS G4, Non-PostScript Printer: Adobe POSScript A: Adobe PDF 17, AP-C24, JP-RTL, TFF, JPEG, CALS G4, Non-PostScript Printer: Adobe PDF 17, AP-C24, JP		
Scan format JPEG, TIFF, PDF (for PestScript Printer) Scan destinations USB, shared network (folder printer HDB, email Wedia		
San destinations USB, shared network folde, printer HDD, email Media Sheet feed, automatic front-loading roll feed, smart roll switching', integrated output stacker, media bin, automatic honzontal cutter San destination Scanners stradigh: through scan paper path for sheet and cardboard originals Sheet size 2710 v 2716 v 914 v 1219 mm Goli size 2710 v 914 mm width, put 200-m length, 3-h core (default) or 2-in core (optional) Standard sheets A4, A3, A2, A1, A0 (A, B, C, D, E) Sammage Goli size Standard sheets Lip to 0.5 mm (Up to 19.7 mil) MpDitations Line drawings: Mago: Orthophotos: Presentations; Renderings Wetmory 128 GB (Rei processing)"; +tard disk Standard, 500 GB (AES-256 encrypted) Connectivity Gigabit Ethernet (1000Base-17), supporting the following standards: TCPIR BootP/DHCP (IPv4 only), DHCP, W S print, ITH WIT v3, MSNA, 90 (v, 24, 34, 34, 34, 46, 46, 40, 40, 40, 40, 40, 40, 40, 40, 40, 40		
Media Sheet feed, automatic front-loading roll feed, smart roll switching', integrated output stacker, media bin, automatic horizontal cutter Scamer: straight: through scan paper path for sheet and cardboard originals 210, 271 or 914, 2119 mm Roll Size 279 to 914, 2719 mm 271, 199 mm Roll Size 279 to 914, 2719 mm 271, 199 mm Roll Size 279 to 914, 2719 mm 271, 199 mm Roll Size 279 to 914, 2719 mm 271, 199 mm Standard sheets Ad, Az, AZ, AJ, AG, KG, LQ, D, D 271, 199 mm Standard Sheets 44, Az, AZ, AJ, AG, KG, LQ, D, D 271, 199 mm Standard Sheets Up to 0. Stand GM, Standard S, CD, DD 271, 199, 711, 199, 7111 Metmory 128 GB file processing? 444 ads 512, 171, 199, 199, 199, 199, 191, 191, 191		
andling Sheet feed, automatic from-loading roll feed, smart roll switching', integrated output stacker, media bin, automatic indicatoria cuter Sciencer: straight through scan paper path for sheet and cardboard originals 210.4 279 (o) 914 × 1219 mm Silvet size 210.4 279 (o) 914 × 1219 mm path core (default) or 2-in core (optional) Standard Sheets A4, A3, A2, A1, A0 (A, B, C, D, D path core (default) or 2-in core (optional) Standard Sheets A4, A3, A2, A1, A0 (A, B, C, D, D path core (default) or 2-in core (optional) Standard Sheets Up to 0.5 mm (Up to 19.7 mill) path core (default) Splitcations Line drawings, Maps, Orthophotos, Presentations; Renderings Memory Vertory 128 GR (Bit processing)": standard, 500 GB (AES-256 encrypted) Connectivity core (default) core (default) path (A2, A2, A2, A1, A2, A		USB, shared network rolder, printer HDD, email
automatic horizontal cutter Scanner straight-Howing scan paper path for sheet and cardboard originals 210 x 279 to 914 x 1219 mm Roll size 270 to 928 g/m ² Roll size 270 to 928 g/m ² Roll size 270 to 914 x 1219 mm Roll size 270 to 914 to 914 x 1219 mm Roll size 270 to 914 to 914 x 1219 mm Roll size 270 to 914 to 914 x 2, SMBv3 Size 270 to 914		Characteristic and an experimental formation and the second and an involve of the second advantage standard and the later
Sheet size 210.x 279 to 914 x 1219 mm Roll size 279 to 914 x 1219 mm Standard sheets Ad, A, A, A, A, O, K, O, K, O, E, D Standard sheets Up to 0.328 g/m² Thickness Up to 0.328 g/m² Thickness Up to 0.328 g/m² Standard sheets Up to 0.328 g/m² Standard sheets Standard sheets Applications Line drawings, Maps, Orthophotos; Presentations; Renderings Memory 128 GB (IIIs processing)* And disk Standard, 500 GB (AES-256 encrypted) Connectivity Gigabit Ethernet (1000Base -T), supporting the following standards: TCP/IR, BootP/OHCP (IPV 4010), SSL/TLS, Boo.21 X authrictation (LEAP, REAP AD-15), DEP Standard PostScript Printer: Adobe PostScript 3, Adobe POF 1.7 Print languages (standard) Pontscript Printer: Adobe PostScript 3, Adobe PDF 1.7 Printing paths Direct printing from US6 Blash drive, print from metwork shared folder, email printing. HP driver for Windows, APP rint for Chrome 05, H Stress PostScript Printer: Raster drivers for Windows, APPrint for MacOS PostScript Printer: State drivers for Windows, APPrint for MacOS Non-PostScript Printer: Raster drivers for Windows, APPrint for MacOS PostSc	nandling	automatic horizontal cutter
Rel Size 279 to 91.4-mm width, up to 200-m length, 3-in core (default) or 2-in core (optional) Standard sheets A4, A3, A2, A1, A0 (A, B, C, D, E) Simmage G0 to 282 g/m ² Thickness Up to 0.5 mm (Up to 19.7 mil) Applications Line drawings: Maps; Orthophotos; Presentations; Renderings Memory 128 GB (file processing)*; Hard disk Standard, 500 GB (AES-256 encrypted) Connectivity Direct only, Spec, SMT (Penkult, Rev IP printing (1010), ED, IP, WS print, NTLM v2, SMB/3, SMD (17, V2, v3), Apple Bonjour Compatible, WS Discovery, Enbedded Web Server (HTTP, HTTPS, JPES, CMTC (Penkult, Rev IP printing (1010), ED, IP, WS print, NTLM v2, SMB/3, SSL/TLS, 802.17 & authentication (LEAP, IPEAP, EAP, TLS), DF Print languages (standard) PoatScript Printer, Adobe PostScript 2, Adobe POF 1.7 Prints opatis Direct printing: More LG Sal Adve, print from network shared folde; email printing, HP driver for Windows, HP Print Service for Android, Apple APPrint driver for macOS and 05, HP Print Script Printer, Adobe POS Script Printer, Marcial, Apple APPrint driver for macOS and 05, HP Print Script Printer, Marcial, Apple APPrint driver for macOS and 05, HP Print Script Printer, MP Script Printer, MARCial PS Script Printer, Adobe POS Script Printer, MP Script Printer,	Shoot cizo	
Standard sheets AI, AI, AI, AI, AI, AI, AI, OK, B, C, D, EI Grammage 60 to 328 g/m ² . Thickness Up to 0.5 mm (Up to 19.7 mil) Applications Line drawings; Maps; Orthophots; Presentations; Renderings Memory 128 GB (Ille processing) ¹ ; and disk Standard, 500 GB (AES-256 encrypted) Connectivity Gigabit Ethernet (1000Base-T), supporting the following standards; TCP/IP BootPDDFC (IPv4 only), MPV fv1, v2c, v31, Apple Bonjour Compatible, WS Discovery, Enchedded Web Server (HTTP HTTPS), Dase; SMT (Pennill, Revi P, printing (9100), LPD, IPP, WS print, NTLM v2, SMBv3, SSL/TLS, 802.1X authentication (LEAP, PEAP, EAP-TLS), DFS Print languages (standard) PostScript Printer: Adobe PostScript 3, Adobe PDF 1.7, HP-GL/2A, HP-RTL, TIFF, JPEG, CALS G4, Non-PostScript Printer, Paster, Standard, Apple AIPPrint driver for macro5 and IOS, HP Print for Chrome 05, HCILS, HP Print 199 Bfash drive, print from network model ond in the main standards in the main standards in the main standards in the main standards in the main standard in		
Grammage 60 to 328 g/m² Thickness Up to 0.5 mm (Up to 19.7 mi) Applications Line drawings; Maps, Orthophotos; Presentations; Renderings Memory 128 GB (file processing)*; Fland disk Standard, 500 GB (AES-256 encrypted) Connectivity Gigabit Ethernet (1000Base-1), supporting the following standards; TCP/IP BootPD/DHCP (IPV4 only), orthophotos; Presentations; Parket (11, V, 26, va), Apple Bonjour Compatible. WS Discovery, Embedded Web Server (NTTP HTTPS), IPSec, CMTP (Encal), Raw IP printing (9100), LPD, IPP, WS print, NTLM v2, SMBv3, SSL/TLS, 802.1X authentication (LEAP, PEAP, EAP-TLS), DFS Print languages (standard) PostScript Printer: Adobe PostScript 2, Adobe PDF 1.7, IP-C-L/2, HP-RTL, TFF, JPEG, CALS G4; Non-PostScript Printer: Adobe PostScript 2, Adobe PDF 1.7 Printing paths Direct printing from USB flash drive, print from network shared folder, email printing, HP driver for Windows, HP Print Server for Android Apple AiPPrint driver for windows, AIPPrint for Chrome OS, Non-PostScript Printer: RostScript Printer: RostScr		
Thickness Up to 0.5 mm (Up to 19.7 mil) Applications Line drawings; Maps; Orthophots; Presentations; Renderings Memory 128 GB (IIIE processing)*; Hard disk Standard, 500 GB (AES-256 encrypted) Connectivity Difference Orthophotographic Supporting the following standards: TCP/IR BootP/DHCP (IPv4 only), DHCPv6, TFTP (Pv4 only), SMPP V1, v2c, v31, Apple Bonjour Compatible, WS Discovery, Enchedded Web Server (HTTP HTTPS), Besc; SMTP (Gmail, Raw IP, printing (9100), LP0, IPP, WS print, NTLM v2, SMBv3, SSL/TLS, 802.1X authentication (LEAP, PEAP, EAP-TLS), DFS Print languages (standard) PostScript Printer: Adobe PostScript 3, Adobe PDF 1.7, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, Non- PostScript Printer: PostScript 3, Adobe PDF 1.7, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, Non- PostScript Printer: PostScript 3, Adobe PDF 1.7, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, Non- PostScript Printer: PostScript and PDF Windows driver, raster drivers for Windows, AirPrint for mcOS Non-PostScript Printer: PostScript and PDF Windows driver, raster drivers for Windows, AirPrint for mcOS Non-PostScript Printer: PostScript and PDF Windows driver, raster drivers for Windows, AirPrint for mcOS Non-PostScript Printer: Raster drivers for Windows, AirPrint for mcOS Non-PostScript Prin	_	
Applications Line drawings; Maps; Orthophotos; Presentations; Renderings Memory 128 GB (file processing)* and disk Standard, SOO GB (AES-256 encrypted) Connectivity DECVor, TTPI (PVA only), SNMP (v1, v2c, v3), Apple Bonjour Compatible, WS Discovery, Embedded Web Server (NTTP, HTTPS), IPsec, SMTP (email), Raw IP printing (1000, LPD, IPP, WS print, NTLM v2, SMBv3, SSL/TLS, 802: 1X automicitation (LEAP, PEAP, EAP-13), DFS Print languages (standard) PostScript Printer: Adobe PostScript 13, Adobe PDF 1.7, LP-GL2, HP-RTL, TTFF, JEF, GLAS G4 Print languages (standard) Non-PostScript Printer: Adobe PostScript 3, Adobe PDF 1.7 Print languages (standard) Non-PostScript Printer: Adobe PostScript Ninter: Rote of there for works shared folder, email printing, HP driver for Windows, HP Print FM G-L2, HP-RTL, TFF, JEF, GLAS G4 Print languages (standard) Non-PostScript Printer: Adobe PostScript Ninters, raster drivers for Windows, AirPrint for macOS: non-PostScript Printer: Postcript and PDF Windows drivers, raster drivers for Windows, AirPrint for macOS: Non-PostScript Printer: Postcript and PDF Windows, AirPrint, Tor macOS and US, SUMPv3, HTTPS, Secure PIP, Psec/Firewall, Certificates management, 802. N, TLS 1.01.11/1.2, HP Web Jetadmin compatible, Social PP, Pieser/Firewall, Certificates management, 802. N, TLS 1.01.11/1.2, HP Web Jetadmin compatible, Becure Box 4 at N 1 Printer Single-roll: 154 kg, dual-roll: 170 kg Single-roll: 154 kg, dual-roll: 70 kg Single-roll: 202 kg, dual-roll: 70 kg		
Memory 128 GB (file processing)*; Hard disk Standard, SDO GB (AES-256 encrypted) Connectivity Gigabit Ethernet (1000Base-T), supporting the following standards: TCP/IP, BootP/DHCP (IPV4 only), DHCPV6, TFTP (IPV4 only), SNMP (V1, VZ, V3, Apple Boniour Compatible, WS Discovery, Embedded Web Server (HTTR, HTTP), IPV5, DPVC, STMP (Enail), Ravi Pprinting (9100), IPD, IPX VS print, NTLW VZ, SMW3, SSL/TLS, B02:1X authentication (LEAP, PEAP, EAP-TLS), DFS Print languages (standard) PostScript Printer: Adobe PostScript 3, Adobe POF 1.7 Printer Direct printing from USB flash drive, print from network shared folder, email printing, HP driver for Windows, HP Print Ser (DS and Android, HP SmattStream (optional) Direct printing from USB flash drive, print from network shared folder, email printing, HP driver for Windows, HP Print Ser (DS and Android, HP SmattStream (DS) Oriest Non-PostScript Printer: PostScript and PDF Windows, AirPrint for macOS Stormer Non-PostScript Printer: Roster drivers for Windows, AirPrint for macOS Security features HP Secure-BOD, Whitelisting, TPM, Role Based Access Control, LDAP and Kerberos authentication, SMMPv3, HTTPS, Secure-IPP, IPPec/Firewall, Certificates management, 802.1X, TLS 10/11/12, HP Web Jetadmin compabile, HP VedWandrage Security Managor compabile, Secure Disk rease (DD S220.22-M), Secure File erase, sel-encrypting HDD, encrypted PIN printing, Sysiog security logging Direter 1500 x 660 x 1310 mm Singing Tic20 x 770 x 1260 mm		
Hard disk Standard, 500 GB (AES-256 encrypted) Connectivity Gigabit Ethernet (1000Base-T), supporting the following standards: TCP/IP BootP/DHCP (IPv4 only), DHCPv6, TFTP (IPv4 only), SNMP (v1, v2c, v3), Apple Bonjour Compatible, W5 Discovery, Embedded Web Server (HTTP, HTTP5), IPsec, SMTP (email), Raw IP printing (1000), LPD, LPD, W5 print, NTLM v2, SMBV3, SSL/TJS, 802.1X Automication (LEBR PEAP, EAP-115), ISFS Print languages (standard) PostScript Printer: Adobe PostScript 3, Adobe PDF 1.7, HP-GL2, HP-RTL, TIFF, JPEG, CALS G4 Print languages (optional) Non-PostScript Printer: Adobe PostScript 3, Adobe PDF 1.7 Print languages (standard) Non-PostScript Printer: Adobe PostScript A, Print, Fry LPG, CALS G4 Print languages (optional) Non-PostScript Printer: Adobe PostScript Printer: Rott Green Stand for (Legreen Control), Apple AlPrint for metwork shared folder, email printing. HP driver for Windows, HP Print PostScript Printer: Rotter drivers for Windows, AirPrint for Chrome 05, H Click, HP Smart App for iOS and Android, HP SmartStream (optional) Printers PostScript Printer: PostScript APD Windows, AirPrint for macOS: Non-PostScript Printer: Rotter drivers for Windows, AirPrint for macOS: Non-PostScript Printer: Rotter driver for macOS: Single		
Connectivity Gigabit Ethemet (1000Base-T), supporting the following standards: TCP/IP BootP/DHCP (IPv4 only), DHCPv6, TTP (IPv4 only), SNMP (v1, v2, v3), Apple Bonjour Compatible, W5 Discovery, Embedded Web Server (HTTP, HTTPS), IPsec, SMTP (email, Raw IP printing (9100), LPD, IPP, WS print, NTLM v2, SMBv3, SSL/TLS, 802.1 Xau thenication (LEAP PEAP EAP T-13, DFS) Print languages (potional) PostScript Printer: HP-GL2, LPN-RTL, TIFF, JPEG, CALS G4 Print languages (optional) Non-PostScript Printer: Adobe PostScript 3, Adobe PDF 1.7 Printing paths Direct printine: Adobe PostScript 3, Adobe PDF 1.7 Printing paths Direct printine: Roster Grix Android, Apple APPrint APrint for acOS Non-PostScript Printer: Roster Grix Android, Apple APPrint APrint for macOS Non-PostScript Printer: Roster Grix Android, Apple APPrint APrint for macOS Non-PostScript Printer: Roster Grix Android, Apple APPrint APrint for macOS Non-PostScript Printer: Roster Grix Android, Apple APPrint APrint for macOS Non-PostScript Printer: Roster Grix Android, Apple APPrint APrint for macOS Non-PostScript Printer: Roster GrixTeRicates management, 802.1 X, T1.5 J Ol.1 / 1.7 J. PH Web Hetadmin compatible, MP letAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypting HDD, encrypted PIN printing, Syslog security logging Dimensions (w x d x h) HP Designlet XL 3600 Multifunction Printer, printere, guide, setup poster, power cord PM Software and solution HP Designlet XL 3600 Multifunction Printer, guide, setup poster, power cord PM Software and solutions HP Designlet XL 3600 Multifunction Printer, guide, s	-	
Interfaces Gigabit Ethernet (1 000Base-T), supporting the following standards: TCP/IB wolf/DHCP (IPv4 only), DHCPv6, TTP (IPv4 only), SMPP Vo1, v2c, v3), Apple Bonginer Compatible, WS Discovery, Embedded Web Server (HTTP, HTP), IPs6, SMPP (Henail), Raw IP printing (9100), UP, IPP, WS print, NTLN v2, SMBv3, SSL/TLS, 802. IX authentication (LEAP, PEAP, EAP-TLS), DFS Print languages (standard) PostScript Printer: Adobe PostScript 7, Adobe POF 1.7 PostScript Printer: HP-GL2, HP-RTL, TIFF, JPEG, CALS G4, Non-PostScript Printer: Adobe PostScript Adobe PostScreat Printer: Adobe PostScript Printer: Robe Robe Postesce Control (LDP Post) Robe Robe Postece: Advantage Sc		Standard, 500 GB (AES-256 encrypted)
DifLPoF, TETP (IPV anyl), SNMP (v1, v2c, v3), Apple Bonjour Compatible, W5 Discovery, Embedded Web Server (HTTP, HTPS), IPPSC, SMTP (Peravil), Rave IP printing (9100), IPO, IPP, WS print, NTLM v2, SMBv3, SSL/TLS, 802.1X authentication (LEAP, PEAP, EAP-TLS), DFS Print languages (standard) PostScript Printer: Adobe PostScript 3, Adobe PDF 1.7, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4 Print languages (optional) Non-PostScript Printer: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4 Print languages (optional) Non-PostScript Printer: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4 Print languages (optional) Non-PostScript Printer: Bash drive, print from network shared folder, email printing, HP driver for Windows, HP Print Service for Android, Apple AiPrint driver for macOS and IOS, HP Print for Chrome OS, H Citck, HP Smart App for IOS and Android, HP SmartStream (optional) Drivers PostScript Printer: Raster drivers for Windows, AirPrint for macOS Non-PostScript Printer: Raster drivers for Windows, AirPrint for macOS Non-PostScript Printer: Raster drivers for Windows, AirPrint for macOS HP Secure Boot, Whitelisting, TPM, Role Based Access Control, LDAP and Kerberos authentication, SNMPA3, HTTPS, Secure-IPB (Psec/Firewall, Certificates management, 802.1X, TLS 1.0/1.1/1.2, HP web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (100 S220.22-A), Secure File erase, self-encrypting HDD, encrypted PIN printing, Syslog security logging Dimensions (w x d x h) Printer	-	
Print languages (standard) PostScript Printer: Adobe PostScript 3, Adobe PDF 1.7, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4; Non-PostScript Adobe PDF 1.7 Print languages (optional) Non-PostScript Adobe PDF 1.7 Printing paths Direct printing from USB flash drive, print from network shared folder, email printing, HP driver for Windows, HP Print Service for Android, Apple AMPPrint driver for macOS and IOS, HP Print for Chrome OS, H Click, HP Smart App for IOS and Android, HP SmartStream (potional) Drivers PostScript Printer: RostScript and Android, HP SmartStream (potional) Drivers PostScript Printer: RostScript and Android, HP SmartStream (potional) Drivers PostScript Printer: RostScript And PDF Windows, AirPrint for macOS Security features HP Secure Boot, Whitelisting, TPM, Role Based Access Control, LDAP and Kerberos authentication, SNMPv3, HTTPS, Secure-IPP, IPsec/Firewall, Certificates management, 802.1%, TLS 100.1/1.1/2, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypting HDD, encrypted PIN printing, Syslog security logging Dimensions (w x d x h) Printer Pinter Single-roll: 154 kg, dual-roll: 170 kg Shipping Single-roll: 202 kg, dual-roll: 218 kg What's in the box HP Designlet XL 3600 Multifunction Printer, printhead, introductory ink cartridges, scanner calibration sheet, 2-in hubright adapter kit, quick reference guide, setup poster, power cord	nterfaces	DHCPv6, TFTP (IPv4 only), SNMP (v1, v2c, v3), Apple Bonjour Compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS), IPsec, SMTP (email), Raw IP printing (9100), LPD, IPP, WS print, NTLM v2, SMBv3,
Print languages (optional) Non-PostScript Printer: Adobe PostScript 3, Adobe PDF 1.7 Printing paths Direct printing from USB flash drive, print from network shared folder, email printing, HP driver for Windows, HP Print Service for Android, Apple AthiPrint driver for macOS and IOS, HP Print for Chrome OS, H Click, HP Smart App for iOS and Android, HP SmartStream (optional) Drivers PostScript Printer: PostScript and PDF Windows drivers, raster drivers for Windows, AiPrint for macOS Security features HP Secure Boot, WhiteIsting, TPM, Role Based Access Control, LDAP and Kenbros authentication, SIMPV3, HTTPS, Secure-IPPR, IPsec/Firewall, Certificates management, 802.1X, TLS 1.0/1.1/1.2, HP Web Jetadmin compabble, HP JeAdvantage Security Manager compabble, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypting HDD, encrypted PIN printing, Syslog security logging Dimensions (w x d x h) Single-roll: 154 kg, dual-roll: 170 kg Printer Single-roll: 202 kg, dual-roll: 218 kg What's in the box HP Designlet XL, 3600 Multifunction Printer, printhead, introductory ink cartridges, scanner calibration sheet, 2-in hubright adapter kit, quick reference guide, setup poster, power cord HP Software and solutions HP Click, HP mobile, ePrint and IOS/Android support plus the HP Smart Tacker (optional) Environmental ranges Operating temperature -25 to 55°C (-11 to 131°F) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 1.9 dB(A) (sleep)	Print languages (standard)	
Printing paths Direct printing from USB flash drive, print from network shared folder, email printing, HP driver for Windows, HP Print Service for Android, Apple AirPrint driver for mac05 and IOS, HP Print for Chrome OS, H Click, HP Smart App for IOS and Android, HP SmartStraem (optional) Drivers PostScript Printer: PostScript and PDF Windows drivers, raster drivers for Windows, AirPrint for mac05 Non-PostScript Printer: Raster drivers for Windows, AirPrint for mac05 Security features HP Secure Book (Whitelisting, TMR, Role Based Access Control, LDAP and Kerberos authentication, SNMPv3, HTTPS, Secure-IPP, IPsec/Firewall, Certificates management, 802, 1X, T.1 /1, Z, HP Web Jetadmin compable, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220, 22-M), Secure File erase, self-encrypting HDD, encrypted PIN printing, Syslog security logging Dimensions (w x d x h) Printer 1500 x 660 x 1310 mm Shipping 1620 x 770 x 1260 mm Weight Printer Single-roll: 202 kg, dual-roll: 218 kg What's in the box HP Designlet XL 3600 Multifunction Printer, printhead, introductory ink cartridges, scanner calibration sheet, 2-in hubright adapter kit, quick reference guide, setup poster, power cord HP Sotymenature 5 to 35°C (41 to 95°F) Socada Security Manager, HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Socia 35°C (41 to 95°F) Socada Security Manager, HP SmartStream (optional), HP SmartTracker (optional) Storage temperature	Print languages (optional)	
Drivers PostScript Printer: PostScript and PDF Windows drivers, raster drivers for Windows, AirPrint for macOS Security features HP Secure Boot, Whitelisting, TPM, Role Based Access Control, LDAP and Kerberos authentication, SNMPv3, HTTPS, Secure-IPP, IPsec/Firewall, Certificates management, 802.1X, TLS 1.0/1.1/1.2, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypting HDD, encrypted PIN printing, Syslog security logging Dimensions (w x d x h) Printer 1500 x 660 x 1310 mm Shipping 1620 x 770 x 1260 mm Weight Printer Single-roll: 154 kg, dual-roll: 170 kg Single-roll: 202 kg, dual-roll: 218 kg What's in the box HP DesignJut XL 3600 Multifunction Printer, printhead, introductory ink cartridges, scanner calibration sheet, 2-in hubright adapter kit, quick reference guide, setup poster, power cord PJ Software and solutions HP DesignJut XL 3600 Multifunction Support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Doperating temperature 5 to 35°C (41 to 95°F) Opperating humidity 20 to 80% RH Storage temperature -25 to 55°C (-13 to 131°F) Accoustics Sound power 5.9 B(A) (operating); 32 dB(A) (idle); < 1.0 B(A) (sleep)		Direct printing from USB flash drive, print from network shared folder, email printing, HP driver for Windows, HP Print Service for Android, Apple AirPrint driver for macOS and iOS, HP Print for Chrome OS, H
Security features HP Secure Boot, Whitelisting, TPM, Role Based Access Control, LDAP and Kerberos authentication, SNMPv3, HTTPS, Secure-IPP, IPsec/Firewall, Certificates management, 80.21, X, TLS 1.0/1.1/1.2, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk rease (DoD 5220.22-M), Secure File erase, self-encrypting HDD, encrypted PIN printing, Syslog security logging Dimensions (w x d x h) Printer 1500 × 660 × 1310 mm Shipping 1620 × 770 × 1260 mm Weight Printer Single-roll: 154 kg, dual-roll: 170 kg Shipping Single-roll: 202 kg, dual-roll: 218 kg What's in the box HP DesignJet XL 3600 Multifunction Printer, printhead, introductory ink cartridges, scanner calibration sheet, 2-in hubright adapter kit, quick reference guide, setup poster, power cord HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 35°C (41 to 95°F) Operating temperature -25 to 55°C (-13 to 131°F) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep)	Drivers	PostScript Printer: PostScript and PDF Windows drivers, raster drivers for Windows, AirPrint for macOS;
Dimensions (w x d x h) Printer 1500 x 660 x 1310 mm Shipping 1620 x 770 x 1260 mm Weight Printer Single-roll: 154 kg, dual-roll: 170 kg Shipping Single-roll: 202 kg, dual-roll: 218 kg What's in the box HP DesignJet XL 3600 Multifunction Printer, printhead, introductory ink cartridges, scanner calibration sheet, 2-in hubright adapter kit, quick reference guide, setup poster, power cord HP Dick, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Diperating temperature 5 to 35°C (41 to 95°F) Operating temperature -25 to 55°C (-13 to 131°F) Acoustics Sound pressure -22 to 55°C (-13 to 131°F) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep)	Security features	HP Secure Boot, Whitelisting, TPM, Role Based Access Control, LDAP and Kerberos authentication, SNMPv3, HTTPS, Secure-IPP, IPsec/Firewall, Certificates management, 802.1X, TLS 1.0/1.1/1.2, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File
Printer 1500 × 660 × 1310 mm Shipping 1620 × 770 × 1260 mm Weight Printer Single-roll: 154 kg, dual-roll: 170 kg Shipping Single-roll: 202 kg, dual-roll: 218 kg What's in the box HP DesignJet XL 3600 Multifunction Printer, printhead, introductory ink cartridges, scanner calibration sheet, 2-in hubright adapter kit, quick reference guide, setup poster, power cord HP Software and solutions HP Click, HP mobile, ePrint and IOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 35°C (41 to 95°F) Operating temperature -25 to 55°C (-13 to 131°F) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep)	Dimensions (w x d x h)	cose, sea che ypang rob, che ypeer ar pratang, systeg seed ty logging
Shipping 1620 x 770 x 1260 mm Weight Single-roll: 154 kg, dual-roll: 170 kg Shipping Single-roll: 202 kg, dual-roll: 218 kg What's in the box HP Designet XL 3600 Multifunction Printer, printhead, introductory ink cartridges, scanner calibration sheet, 2-in hubright adapter kit, quick reference guide, setup poster, power cord HP Software and solutions HP Click, HP mobile, ePrint and IOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Deperating temperature 5 to 35°C (41 to 95°F) Operating humidity 20 to 80% RH Storage temperature -25 to 55°C (-13 to 131°F) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep)		1500 x 660 x 1310 mm
Weight Printer Single-roll: 154 kg, dual-roll: 170 kg Shipping Single-roll: 202 kg, dual-roll: 218 kg What's in the box HP DesignJet XL 3600 Multifunction Printer, printhead, introductory ink cartridges, scanner calibration sheet, 2-in hubright adapter kit, quick reference guide, setup poster, power cord HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Deparating temperature 5 to 35°C (41 to 95°F) Operating humidity 20 to 80% RH Storage temperature Storage temperature -25 to 55°C (-13 to 131°F) Accoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep)		
Printer Single-roll: 154 kg, dual-roll: 170 kg Shipping Single-roll: 202 kg, dual-roll: 218 kg What's in the box HP DesignUet XL 3600 Multifunction Printer, printhead, introductory ink cartridges, scanner calibration sheet, 2-in hubright adapter kit, quick reference guide, setup poster, power cord HP Software and solutions HP Click, HP mobile, ePT int and IOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Dperating temperature 5 to 35°C (41 to 95°F) Operating tumperature 5 to 35°C (-13 to 131°F) Accoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep)		
Shipping Single-roll: 202 kg, dual-roll: 218 kg What's in the box HP DesignUet XL 3600 Multifunction Printer, printhead, introductory ink cartridges, scanner calibration sheet, 2-in hubright adapter kit, quick reference guide, setup poster, power cord HP Click, HP mobile, ePT runt and IOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges	-	Single-roll: 154 kg, dual-roll: 170 kg
What's in the box HP DesignJet XL 3600 Multifunction Printer, printhead, introductory ink cartridges, scanner calibration sheet, Z-in hubright adapter kit, quick reference guide, setup poster, power cord HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Dperating temperature 5 to 35°C (41 to 95°F) Dperating temperature -2 to 55°C (-13 to 131°F) Accoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep)		
sheet, Z-in hubright adapter kit, quick reference guide, setup poster, power cord HP Software and solutions HP (Lick, HP mobile, ePrint and iOS/Android Support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Diperating temperature 5 to 35°C (41 to 95°F) Operating temperature 2 to 80% RH Storage temperature -25 to 55°C (-13 to 131°F) Accoustics Sound pressure 30und pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep)		
HP JetAdvantage Security Manager, HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 35°C (41 to 95°F) Operating humidity 20 to 80% RH Storage temperature -25 to 55°C (-13 to 131°F) Acoustics -25 to 55°C (-13 to 131°F) Acoustics -25 to 55°C (-13 to 9 B(A) (idle); < 19 dB(A) (sleep)		sheet, 2-in hubright adapter kit, quick reference guide, setup poster, power cord
Operating temperature 5 to 35°C (41 to 95°F) Operating humidity 20 to 80% RH Storage temperature -25 to 55°C (-13 to 131°F) Acoustics	HP Software and solutions	
Operating humidity 20 to 80% RH Storage temperature -25 to 55°C (-13 to 131°F) Acoustics	-	
Storage temperature -25 to 55°C (-13 to 131°F) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep)		
Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep)		
Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep)		-25 to 55°C (-13 to 131°F)
Sound power 5.9 B(A) (operating); 4.9 B(A) (idle); < 3.7 B(A) (sleep) Power Sound power Consumption < 120 W (printing + scanning); 40 W (ready); < 1.0 W (< 14 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); India (BIS) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Austra (ACMA), New Zealand (RSM), China (CCC), Japan (VCC), Korea (KCC) Environmental ENERGY STAR; WEEE; RoHS (EU, China, Korea, India); REACH; EPEAT	Acoustics	
Consumption < 120 W (printing + scanning); 40 W (ready); < 1.0 W (< 14 W with embedded Digital Front End) (sleep);	ound pressure	
Consumption < 120 W (printing + scanning); 40 W (ready); < 1.0 W (< 14 W with embedded Digital Front End) (sleep);	Sound power	5.9 B(A) (operating); 4.9 B(A) (idle); < 3.7 B(A) (sleep)
0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); India (BIS) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Austra (ACMA), New Zealand (RSM), China (CCC), Japan (VCC), Korea (KCC) Enveronmental ENERGY STAR; WEEE; RoHS (EU, China, Korea, India); REACH; EPEAT		< 120 W (printing + scanning); 40 W (ready); < 1,0 W (< 14 W with embedded Dinital Front Ford) (cleen):
Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); India (BIS) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Austra (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC) Environmental ENERGY STAR; WEEE; ROHS (EU, China, Korea, India); REACH; EPEAT		
Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); India (BIS) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Austra (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC) Environmental ENERGY STAR; WEEE; ROHS (EU, China, Korea, India); REACH; EPEAT	Requirements	Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A
Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); India (BIS) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Austra (ACMA), New Zealand (RSM), China (CCC), Japan (VCC), Korea (KCC) Environmental ENERGY STAR; WEEE; RoHS (EU, China, Korea, India); REACH; EPEAT		
Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Austra (ACMA), New Zealand (RSM), China (CCC), Japan (VCC), Korea (KCC) Environmental ENERGY STAR; WEEE; RoHS (EU, China, Korea, India); REACH; EPEAT	Safety	
Environmental ENERGY STAR; WEEE; RoHS (EU, China, Korea, India); REACH; EPEAT	Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Austral
	Environmental	

Ordering information

Product 6KD23A

Product	
6KD23A	HP DesignJet XL 3600 36-in Multifunction Printer
6KD24A	HP DesignJet XL 3600 36-in Multifunction Printer with PostScript/PDF
6KD25A	HP DesignJet XL 3600dr 36-in Multifunction Printer
6KD26A	HP DesignJet XL 3600dr 36-in Multifunction Printer with PostScript/PDF
Accessories	
3JJ54A	HP F40 Folder
6CC86A	HP SmartTracker USB for HP XL 3000 Printer series
6CC86AAE 6SE87A	HP SmartTracker for HP XL 3000 Printer series HP DesignJet XL 3600 MFP Folder Upgrade Kit
6SE88A	HP SmartStream Print Controller USB for HP XL 3000 Printer series
6SE88AAE	HP SmartStream Print Controller for HP XL 3000 Printer series
COC66C	HP DesignJet PostScript/PDF Upgrade Kit
L3J69A	HP SmartStream USB Preflight Manager
L3J69AAE	HP SmartStream Preflight Manager
	printing supplies
B3P06A	HP 727\732 Designjet Printhead
3ED52A	HP 766B 300ml Yellow DesignJet Ink Cartridge
3ED53A 3ED54A	HP 766B 300ml Magenta DesignJet Ink Cartridge HP 766B 300ml Cyan DesignJet Ink Cartridge
3ED54A 3ED55A	HP 766B 300ml Cyan DesignJet Ink Cartridge HP 766B 300ml Photo Black DesignJet Ink Cartridge
3ED55A	HP 766B 300ml Gray DesignJet Ink Cartridge
3ED57A	HP 766B 300ml Matte Black DesignJet Ink Cartridge
	IP inks and printheads, and HP large format printing materials,
	consistent high quality and reliable performance that enable less
	nese critical components are designed and engineered together as an
optimized pri	nting system, and Original HP inks are designed to maximize the life of
	s. Protect your HP printer investment by using Original HP inks for full HF
	tection. For more information, visit hp.com/go/OriginalHPinks.
	arge format printing materials
	right White Inkjet Paper (FSC® certified) (recyclable) 914 mm x 91.4 m
(36 in x 300 f	:) bated Paper (PEFC™ certified) (recyclable) 914 mm x 91.4 m
(36 in x 300 f	
	,, niversal Heavyweight Coated Paper, 3-in Core (FSC® certified) ⁵ (recyclable)
	4 m (36 in x 300 ft)
D9R28A HP E	veryday Matte Polypropylene, 3-in Core 914 mm x 61 m
(36 in x 200 f	:)
Service and	Support
	-year NBD HW Support with DMR
	-year NBD HW Support with DMR
	-year NBD HW Support with DMR
	1-year Post Warranty NBD HW Support with DMR 2-year Post Warranty NBD HW Support with DMR
	stallation Service with Network Setup
	Support Services offer installation, maintenance, and extended support 2, 3, 4 and 5 years). For more information, please visit hp.com/go/cpc
	HP Large Format Printing Materials portfolio, please see HPLFMedia.com.
ECO highligh	
	with automatic print settings and image nesting
	AR® certified ¹ and EPEAT® registered ²
 Free, conve 	nient HP ink cartridge recycling ³
 FSC[®]-certifi 	ed papers4, recyclable HP media; some HP media eligible for takeback
program ⁵	
	e large-format printing hardware and printing supplies.
	at our website hp.com/ecosolutions
	R and the ENERGY STAR mark are registered trademarks owned by the
	iental Protection Agency.
	stered where applicable. EPEAT registration varies by country. See
	peat.net for registration status by country. silability varies. Please check http://www.hp.com/recycle for details.
⁴ BMG tradem	ark license code FSC®-C115319, see http://www.fsc.org. HP trademark
license code F	SC®-C017543, see http://www.fsc.org. Not all FSC®-certified products are
	l regions. For information about HP large format printing materials, please
visit http://wv	vw.HPLFMedia.com.
	IP papers can be recycled through commonly available recycling
	according to region-specific practices. Some HP media are eligible for
return throug	h the HP Large Format Media take-back program. Programs may not

- Save p
 ENERG

- Free, c
 FSC[®]-c progra

Please re Find out

programs, or according to region-specific practices. Some HP media are eligible return through the HP Large Format Media take-back program. Programs may r exist in your area. See http://www.HPLFMedia.com/hp/ecosolutions for details.

¹ Mechanical printing time. Printed in Fast mode with Economode on, using HP Bright White Inkjet Paper (bond) and Original HP inks.
² ±0.1% of the specified vector length or ±0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on A0/E HP Matte Film in Best or Normal mode with Original HP inks.

³ Measured on HP Matte Film.

⁵ Measured on HP Matte Film.
⁶ Based on 8 GB RAM.
⁵ BMG trademark license code FSC®-C115319, see http://www.fsc.org. HP trademark license code FSC®-C107543, see http://www.psc.org. BMG trademark license code FSC®-C017543, see http://www.psc.org. HP trademark license code FSC®-C115319, see http://www.psc.org. HP trademark license code FSC®-C115319, see http://www.psc.org. Not all FSC®- or PEFC®-certified products are available to all the set of th

⁶ Can be recycled through commonly available recycling programs.
 ⁷ Applicable for dual-roll printers only.





© Copyright 2019 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

